

# SPECIFICATIONS

## SPEAKER SYSTEMS

### SP 161 X

### SP 131 X

	Tweeter	Woofers/Midrange	Tweeter	Woofers/Midrange
Cone Material	Woven Silk	Polypropylene	Woven Silk	Polypropylene
Voice Coils	25 mm Aluminum	25 mm Aluminum	25 mm Aluminum	25 mm Aluminum
Frequency Response (Hz)	5,000 - 22,000	70 - 5,000	5,000 - 22,000	80 - 5,000
Diameter Euro-Standard (mm - in.)	47 - 1 7/8	165 - 6 1/2	47 - 1 7/8	130 - 5 1/8
Mounting Depth (mm - in.)	24 - 1	73 - 2 7/8	24 - 1	68 - 2 3/4
Impedance ( $\Omega$ )	4	4	4	4
Mounting	Surface/Flush	Flush	Surface/Flush	Flush

### Crossover

Crossover Slope (Selectable)	6 / 12 dB/Octave			
Crossover Frequency	5,000 Hz			
Impedance ( $\Omega$ )	4		4	
Maximum Power (W)	110		90	
Continuous Power (W)	70		60	

## COAXIAL SPEAKERS

### SP 161 COAX

### SP 131 COAX

### SP 101 COAX

	SP 161 COAX	SP 131 COAX	SP 101 COAX
Cone Material	Tweeter: FC (Ferro Fluid); Woofers/Midrange: Polypropylene		
Switchable Treble Attenuation (dB)	3	3	3
Maximum Power (W)	100	80	60
Continuous Power (W)	50	40	30
Frequency Response (Hz)	55 - 20,000	60 - 20,000	65 - 20,000
Impedance ( $\Omega$ )	4	4	4
Diameter Euro-Standard (mm - in.)	165 - 6 1/2	130 - 5 1/8	100 - 4
Mounting Depth (mm - in.)	75 - 3	70 - 2 3/4	55 - 2 1/4
Optional Cover	•	•	•
Mounting	Flush	Flush	Flush