



SP 161 X SPEAKER SYSTEM

Continuous Power: 70 W
Frequency Response: 70-22,000 Hz
Impedance: 4 Ω
Woofer/Midrange:
Diameter: 6 1/2 in., Mounting Depth: 2 7/8 in.
Tweeter:
Diameter: 1 7/8 in., Mounting Depth: 1 in.

SP 131 X SPEAKER SYSTEM

Continuous Power: 60 W
Frequency Response: 80-22,000 Hz
Impedance: 4 Ω
Woofer/Midrange:
Diameter: 5 1/8 in., Mounting Depth: 2 3/4 in.
Tweeter:
Diameter: 1 7/8 in., Mounting Depth: 1 in.



SP 161 COAXIAL

Continuous Power: 50 W
Frequency Response: 55-20,000 Hz
Impedance: 4 Ω
Diameter: 6 1/2 in.
Mounting Depth: 3 in.

SP 131 COAXIAL

Continuous Power: 40 W
Frequency Response: 60-20,000 Hz
Impedance: 4 Ω
Diameter: 5 1/8 in.
Mounting Depth: 2 3/4 in.

SPEAKER SYSTEMS

SP 161 X

SP 131 X

	Tweeter	Woofers/Midrange	Tweeter	Woofers/Midrange
Cone Material	Woven Silk	Polypropylene	Woven Silk	Polypropylene
Voice Coils	25 mm Aluminum	25 mm Aluminum	25 mm Aluminum	25 mm Aluminum
Frequency Response (Hz)	5,000 - 22,000	70 - 5,000	5,000 - 22,000	80 - 5,000
Diameter (mm - in.)	47 - 1 7/8	165 - 6 1/2	47 - 1 7/8	130 - 5 1/8
Mounting Depth (mm - in.)	24 - 1	73 - 2 7/8	24 - 1	68 - 2 3/4
Impedance (Ω)	4	4	4	4
Mounting	Surface/Flush	Flush	Surface/Flush	Flush

Crossover

Crossover Slope (Selectable)	6 / 12 dB/Octave	
Crossover Frequency	5,000 Hz	
Impedance (Ω)	4	4
Maximum Power (W)	110	90
Continuous Power (W)	70	60

COAXIAL SPEAKERS

SP 161 COAX

SP 131 COAX

SP 101 COAX

Cone Material	Tweeter: FC (Ferro Fluid); Woofers/Midrange: Polypropylene		
Switchable Treble Attenuation (dB)	3	3	
Maximum Power (W)	100	80	60
Continuous Power (W)	50	40	30
Frequency Response (Hz)	55 - 20,000	60 - 20,000	65 - 20,000
Impedance (Ω)	4	4	4
Diameter - Euro-Standard (mm - in.)	165 - 6 1/2	130 - 5 1/8	100 - 4
Mounting Depth (mm - in.)	75 - 3	70 - 2 3/4	55 - 2 1/4
Optional Cover	•	•	•
Mounting	Flush	Flush	Flush